

WLAN-T+

TEMPERATURE DATA LOGGING



FEATURES

- * TEMPERATURE DATA LOGGING SENSOR WITH INTEGRATED DISPLAY
- * EASY SENSOR SET-UP USING THE FREE PC SOFTWARE APPLICATION
- * WIRELESSLY STREAM DATA TO PC VIA WIFI
- * VIEW AND ANALYSE MULTIPLE SENSORS, INCLUDING IMMEDIATE GRAPHING OF HISTORIC DATA
- * SELECTABLE MEASUREMENT SCALE °C / °F
- * TEMPERATURE ACCURACY $\pm 0.1^{\circ}\text{C}$ (-10 TO $+60^{\circ}\text{C}$)
- * TEMPERATURE MEASUREMENT RESOLUTION TO 0.01°C
- * TEMPERATURE DISPLAY RESOLUTION TO 0.01°C
- * TEMPERATURE MEASUREMENT RANGE -20 TO $+60^{\circ}\text{C}$ (-4 TO $+140^{\circ}\text{F}$)
- * OPERATING TEMPERATURE RANGE -20 TO $+60^{\circ}\text{C}$ (-4 TO $+140^{\circ}\text{F}$)
- * CONFIGURABLE HIGH AND LOW ALARMS WITH INDICATOR
- * MAXIMUM AND MINIMUM READINGS
- * LOW BATTERY INDICATOR
- * WIFI CONNECTION INDICATOR / SIGNAL STRENGTH INDICATOR
- * 802.11B COMPLIANT
- * PROTECTION RATING IP55
- * RECHARGEABLE INTERNAL LITHIUM POLYMER BATTERY
- * SENSOR MEMORY STORES ALL DATA EVEN IF WIFI IS TEMPORARILY DISCONNECTED
- * USB PORT USED FOR RECHARGING (CAN ONLY BE RECHARGED WITHIN $0 - 40^{\circ}\text{C}$)
- * FIRMWARE UPGRADABLE VIA USB (DOWNLOADABLE FROM THE WEBSITE)
- * PC CAN BE SWITCHED OFF WITHOUT LOSS OF DATA
- * SUPPLIED WITH WALL BRACKET AND MICRO USB LEAD
- * SUPPORTED SECURITY PROTOCOLS WEP, WPA/WPA2 - PSK

ORDERING CODE

WIFI HIGH ACCURACY TEMPERATURE DATA LOGGING

EA WLAN-T+

GENERAL

The EA WLAN-T+ measures the temperature of the environment in which it is situated. This high accuracy sensor is typically accurate to $\pm 0.1^{\circ}\text{C}$ (0 to $+60^{\circ}\text{C}$). Data is streamed wirelessly over any WiFi network and can be viewed on a PC using our free software package. During configuration, the sensor will search for an existing wireless network whilst physically connected to the PC.

It can then be placed anywhere within range of the network. If the sensor temporarily loses connectivity with the network, it will log readings until it is able to communicate again with the PC application (max 30 days at 10 second sample interval).

The EA WLAN-T+ is a battery powered device with an internal rechargeable lithium polymer battery. The LCD display includes several features including Max and Min readings and indicators for low battery, alarms, WiFi connection and signal strength. The sensor is IEEE 802.11b compliant, supports WEP, WPA/WPA2 encryption and enterprise networks (MS-CHAPv2, PEAP, EAP-FAST, EAP-TTLS).

Setting up your EA WLAN-T+ is easy, using our free PC software. Choose to store your data locally on the PC. You'll be able to view historic data in graphs or tables, and export it in various formats. At any time, you can change the sensor settings, including Name, $^{\circ}\text{C}/^{\circ}\text{F}$, Sample Rate, and High/Low alarm levels. Our software and firmware updates are for free. EA WLAN-T+ has a protection rating of IP55.

The unit is freestanding, but can be attached to a wall or surface using the bracket provided.

Specifications	Minimum	Typical	Maximum	Unit
Battery life		>6*		Months
USB supply voltage	4.5	5	5.5	Vdc
Operating temperature range	-20 (-4)		+60 (+140)	$^{\circ}\text{C}$ ($^{\circ}\text{F}$)
Logging Period (user configurable)	10 sec	10 min	12 hrs	
Transmission Period (user configurable)	1 min	1 hr	24 hrs	
Temperature measurement range	-20 (-4)		+60 (+140)	$^{\circ}\text{C}$ ($^{\circ}\text{F}$)
Temperature measurement resolution		0.01		$^{\circ}\text{C}$
Temperature display resolution		0.01		$^{\circ}\text{C}$
Temperature accuracy (-10 to $+50^{\circ}\text{C}$)		$\pm 0.1^{\circ}\text{C}$ (0 to $+60^{\circ}\text{C}$)	$\pm 0.15^{\circ}\text{C}$ (-20 to $+60^{\circ}\text{C}$)	$^{\circ}\text{C}$

Warning - do not exceed operating temperatures

DIMENSION



all dimensions are in mm